

VISUAL COMFORT & Co.

OL8600RSZ-L1: Small LED Lantern



Dimensions:

Width: 9.0"
Height: 9.69"
Weight: 1.48 lbs.

Extends: 10.375'
Wire: 8" (color;Black/White)
Connection: Mounted To Box
Bulb Type: Modules
Bulb Type: Integrated
Volts: 120
Watts: 14
Watts Consumed: 14
Watts Rated: 14
Hours Rated: 50000
Lumens: 1000
Bulb Temp: 2700 °K
CRI: 90

Collection: Redding Station

Shade interior is Restoration Bronze

Supplied with 8-inches of wire

Designed with a back plate to allow for easy installation

LED is a rapidly-developing lighting technology that cuts energy use by more than 80 percent

Designed for damp and wet environments allowing for direct water contact

5-year manufacturer warranty

UPC #:014817582444

Finish: Restoration Bronze (RSZ)

Bulbs:

1 - LEDIntegrated Modules 14.0w Max. 120v included

Features:

- Dark Sky friendly. Designed to emit no light above the 90° horizontal plane. Photometry unavailable.
- Advanced LED technology that warms in color when dimmed (2700K - 2200K).
- Meets Title 24 energy efficiency standards
- Title 24 compliant high efficacy light source that is not required to be listed in the California Energy Commission Appliance database.

Material List:

1 Body - Aluminum - Undefined

Safety Listing:

Safety Listed for Wet Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (OL8600-OL8601-OL9004-L1)
Trilingual (English, Spanish, and French) (920OL8600 + OL8601 + OL9004)
Trilingual (English, Spanish, and French) (920OL8600-OL8601-OL9004)
Trilingual (English, Spanish, and French) (OL8600 OL8601 OL9004)
Trilingual (English, Spanish, and French) (ol8600)

Backplate / Canopy Details:

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Back Plate	6.5	4.5	1.0		4.25	

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	OL8600RSZ-L1	1	014817582444	13.0	12.5	11.75	1.1	3.1	0	Yes
Master Pack	OL8600RSZ-L1	0	10014817582441							No
NJ Pallet		72		48.0	40.0	77.0	85.56	223.2		No
NV Pallet		72		48.0	40.0	77.0	85.56	223.2		No