

INTERVALS®

20QWL04C

Intervals® is an LED-integrated linear architectural lighting system that blends old-world elegance with new-world minimalism. Architecturally scaled, the suspended horizontal beams are supported from slender ceiling-mounted cables or stems. Short cylindrical glass shades are mounted at equidistance along the frame, providing bidirectional illumination. Intervals® is available in five configuration: with Satin White or Satin Black finish options.

FINISHES

Satin White

DIMENSIONS / SPECS

Height: 11.5"
Width/Diameter: 48.25"
Length: 4"
Minimum Height: 14.25"
Maximum Height: 86.25"
Canopy/Backplate: 4.5"
Hanging Type: 6' Adjustable Cable
Product Weight: 28lb
Canopy/Backplate Shape: Round
Sloped Ceiling Compatible: Yes
Living Finish: No
Uplight Only: No


Shade 1: Glass
Shade 1 Finish: Clear
Shade 1 Top Width: 3"
Shade 1 Height: 4"
Shade 2: Aluminum
Shade 2 Finish: Satin White
Shade 2 Top Width: 3"
Shade 2 Height: 0.75"

ELECTRICAL



Bulb 1
Bulb Included: N/A
Socket: Integrated LED
Bulb Type: LED
Max Wattage: 5
Bulb Quantity: 3
Dimmer Type: ELV, TRIAC, 0-10 VOLT
Gem Box Required (2"x3"): No
Dark Sky: No
CRI: 90
Color Temp.: 3000k
Lumens: 3031
Title 24: No
Field Serviceable: No
Initial Lumens: 4330
IP Rating: N/A

Bulb 2
Bulb Included: N/A
Socket: Integrated LED
Bulb: LED • 3 • 10 Watt Max
Voltage: 120-277V
UL Rating: cETL Damp



INTERVALS®

20QWL04C

SHIPPING

Carton 1: 0" x 0" x 0"

Carton 1 Weight: 0lb

Shipping Method: Ground

Country of Origin: