

MANOR SMALL SCONCE

DJW1061

General Product Information



Intertek



SAVE THESE INSTRUCTIONS!




STANDARD INSTALLATION



INDOOR



DAMP LOCATION SAFE



NEC COMPLIANT JUNCTION BOX



BULB(S) (NOT INCLUDED)



CONVERTS TO LED



DIMMER COMPATIBLE



BEST PRACTICE: HANDLE FIXTURE WITH GLOVES



CLEAN WITH SOFT, DRY CLOTH ONLY. NO HARSH CHEMICALS!



PLEASE SEE visualcomfort.com FOR PRODUCT SPECS



Product Warranty



FCC Statement

Suggested/Required Tools



ELECTRIC DRILL



PHILLIPS-HEAD SCREWDRIVER



WIRE CUTTER

Safety Information

CAUTION-RISK OF FIRE


This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.


USE MINIMUM 90°C SUPPLY CONDUCTORS.



Turn off electrical current at the source before working with any lighting fixture or portable lamp.

Install and use this product in adherence with local electrical codes and regulations.





FIXTURE PARTS

- A. Junction Box
- B. Mounting Plate
- C. Wire Nut Connections
- D. Mounting Screws
- E. Fixture Base
- F. Fixture Screws
- G. Shade
- H. Bulb (Not Included)
- I. Socket
- J. Lower Stem

INSTRUCTIONS

I. Preparing the Fixture

1. Secure the mounting plate to the junction box.

II. Wiring the Fixture

1. Safety first! Locate the circuit breaker and switch it off to cut off the power supply to the relevant circuits to ensure there's no electricity running through the wiring.
2. In accordance with local electrical codes, connect the fixture ground wire (bare copper or silver wire) to suitable ground. This may be a green ground screw on the mounting plate, which the ground wire should be tightly wrapped around or a house wire (green or bare copper wire without insulation).
3. Twist the bare ends of the following pairs of wires together using a wire nut to secure a connection:
 - a) Hot fixture wire to hot power line wire
 - b) Neutral fixture wire to neutral power line wire
4. Carefully tuck all the wires behind the mounting plate into the junction box.

III. Installing the Fixture

1. Place the fixture canopy onto the mounting plate.
2. Use the screws to secure the canopy to the mounting plate.
3. Install the shade by sliding it over the socket.
4. Screw the bulb into the socket. Refer to the socket label for max wattage information.
5. Install the lower stem.