

HARDWIRING ASSEMBLY INSTRUCTIONS FOR Swirl Flush Mount

Model # 3254-21

3254-21

1.0

BEFORE STARTING- SHUT OFF BREAKER AT MAIN DISCONNECT


Make sure all power is disconnected at existing fixture and that there are no live wires in the junction box.

Not all junction boxes include simple wiring. If you are unsure or have doubts of electrical connection, call an electrician for assembly.

Remove all items from the packaging.


Step 1.

Remove 2 screw (B) from the canopy (C) and bracket (A) as shown.




Step 3.

Place bracket (A) to wall. Align hole in bracket (A) with holes in junction box and secure with 2 screws (E) by a phillips head screwdriver. Be sure mounting cross bar is attached tightly to the junction box so the lamp sits sturdy on the wall.



Step 4.

Push all wire connections into junction box. Push up the canopy (C) to cover bracket (A) properly and fasten with the 2 screws (B) separately to tighten.




Step 2.

(1) Twist both ground wire (copper or green) in junction box and in bracket (A) to green grounding bolt ("G").

(2) Attach the neutral fixture wire ("N") from the canopy (C) to the neutral wire in junction box (usually white).

(3) Attach the hot fixture wire ("L") from the canopy (C) to the hot wire in junction box (usually black).

Cover the connected wires with wire nut (D) - tighten each connection by turning clockwise.



GENERAL PRODUCT INFORMATION:

This product is suitable for dry locations only.




IMPORTANT SAFETY INSTRUCTIONS:

This portable lamp has a polarized plug (one blade is wider than the other) as a feature to reduce the risk of electric shock. This plug will fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified electrician. Never use with an extension cord unless plug can be fully inserted. DO NOT ALTER THE PLUG.

BULB TYPE: (1) 60 watt incandescent or 9 watt LED bulb (not included)

Step 5.

Socket ring (F) comes pre-assembled to the socket. Before assembling the shade, please unscrew this socket ring (F). Set shade (E) onto socket and tighten clockwise with socket ring (F) to secure shade.



PARTS DIAGRAM:

