



(This fixture is Damp rated)

How to Install

- 1.** Do a complete inventory of all parts and components before you start installing.
- 2.** Fasten mounting plate to outlet box with the screws supplied.
Place fixture against mounting surface allowing the machine screws to pass through the backplate, then screw with ball nut.
- 3.** After safely attaching fixture into outlet box ,install bulbs and proceed to connecting the power.
- 4.** When you begin to dress the fixture, start with package labeled(A).
- 5. IMPORTANT:**Apply crystal sets in alphabetical order.

Crystal Sets

- A. 1set 6*14mm+1*76mm drop
- B. 2sets 3*14mm+1*76mm drop
- C. 2sets 21*14mm
- D. 1set 15*14mm
- E. 1set 11*14mm+1*76mm drop
- F. 1set 12*14mm+1*76mm drop
- G. 1set 13*14mm+1*76mm drop



⚠ WARNING: This product can expose you to Lead, which is known to the State of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov



PART NUMBER MODEL #ARC-1902-SA-CL-MWP

Part Number

Part Numbers

- A. (1)-Mounting Plate
- B. (2)-Ball Nut(XBN1900SABANUT)
- C. (2)-Scroll arm;L21 1/5"
- D. (1)-Backplate;W8.5*H4.5*D0.85"
(XBN1902SABKP8.5IN)
- E. (2)-Candle Sleeve;L2 4/5"
(XBN1902SACDL2.8IN)

